

ExStik® II DO/pH/Conductivity Kit

User friendly kit economically measures 6 parameters

Features:

- Convenient DO/pH/Conductivity Kit with all the accessories and carrying case for easy travel
- Measures 6 parameters including Dissolved Oxygen, pH, Conductivity, TDS, Salinity, and Temperature
- Designed for water, wastewater, groundwater, aquaculture and fisheries professionals

Kit includes:

- EC500 pH/Conductivity ExStik® II meter with combination high accuracy multi-ranging Conductivity sensor for Conductivity, TDS, Salinity, pH and Temperature measurements
- DO600 Dissolved Oxygen ExStik® II meter with electrode, replacement membrane cap, electrolyte, and polishing paper

Accessories included:

- Sample pH buffers - Single use pouches for pH4, pH7, pH10, and rinse solutions
- Weighted base with 2 cups and caps, 1.5V SR44W batteries and neckstrap with each meter, and carrying case



CE

Specifications:	
Conductivity:	0 to 199µS, 200 to 1999µS, 2.00 to 19.99mS
TDS/Salinity:	0 to 99.9ppm (mg/L), 100 to 999ppm (mg/L) 1.0 to 9.99ppt (g/L)
pH:	0.00 to 14.00pH
DO (saturation mode)	0 to 200.0%
DO (concentration mode)	0 to 20.00ppm (mg/L)
Temperature:	32 to 149°F (0 to 65°C)
DO (concentration mode)	0 to 20.00ppm (mg/L)
Automatic Temp Compensation: Yes	
Max Resolution:	DO600: 0.1%, 0.01ppm (mg/L) EC500: 0.1µS, 0.01ppm (mg/L)
Basic Accuracy:	DO600: ±2.0%FS, 0.4ppm (mg/L) ±1.8°F/1°C EC500: ±2.0%FS, 0.01pH, ±1.8°F/1°C
Dimensions	9.5x 6.8x2.8" (241 x173 x 71mm)
Weight:	1.56 lbs. (708g)

Ordering Information:

DO610ExStik® II DO/pH/Conductivity Kit
 EX010.....Extension Cable, 3ft (1 Meter) with probe weight for ExStik
 EX050.....Extension Cable, 16ft (5 Meter) with probe weight for ExStik

EXTECH INSTRUMENTS CORPORATION
 285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
 Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

"Make mine an Extech!"™
www.extech.com



10/06/04 - R1